

presto Rust and Corrosion Protection Primer

Technical Information



presto Primer stops corrosion and, due to its good filling properties, provides the ideal substrate for the subsequent top coat with all known painting systems. Available in the colors gray and red-brown.

Can be used as a primer for car painting, but also in the hobby area for coating and preserving pipes, machines, radiators, etc.

Ord.-no: 387276, 387290, 387283, 387306

Quality & properties

Permanent anti-corrosion effect
Excellent adhesion to metal
Can be coated with lacquer
Prevents rust and blistering

Physical & chemical data

Base: Acrylic resin
Colourname:
◦ grey
◦ red-brown
Efficiency:
◦ 200 ML – 2-2.5 m²
◦ 750 ML – 7-9 m²
Dry to touch: 45-60 min
Dust dry: 15-20 min
Completely dry: 2-3 d
Overcoatable: 30 min
Surfaces: metal
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 30 °C
Flash point: -4
Storage stability: 1 y
Content:
◦ 200 ML
◦ 750 ML

How to use

The surface has be clean and free of grease.
Stirr well before application.
Apply presto Primer in the desired layer thickness in several steps.
After it has dried completely, sanding with 400 grit sandpaper is possible.
A top coat with any desired type of paint is possible.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.