

presto Silicone Remover

Technical Information



presto Silicone Remover is essential for professional paintwork results because it thoroughly removes dirt, grease, oil, silicone, wax, tar, adhesive residues etc. presto silicone remover saves a great deal of time because it is quick and easy to use and universally applicable. It enhances adhesion for subsequent coatings.

Application areas:

Ideal for spot repairs and refinishing parts, as well as all work that requires a professional clean.

Ord.-no: 458668

Quality & properties

- Simple application
- Extremely time saving
- Mild, non-aggressive solvent
- Thorough removal of silicone, grease, oil, wax, dirt, tar, adhesive residues etc
- Improves adhesion of subsequent coatings

Physical & chemical data

- Base: Special resin
- Colourname: transparent
- Surfaces: primed and filled areas, metal, glass, old paints and original paints from supplier painted and unpainted surfaces
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 500 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can briefly.
- Spray to test.
- Spray at a distance of 20 - 25 cm.
- Spray evenly the surface with Silicone Remover and wipe off with a clean, dry paper towel.
- If heavily soiled, repeat the procedure.
- Let evaporate well the cleaned surfaces.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.