

presto Cut- and Drill Oil

Technical Information



High quality spray oil to reduce the frictional forces when drilling, turning, milling or cutting. Permanently prevents overheating of tools (drills and dies). presto Cut- and Drill Oil protects and lubricates the tool, reducing wear on it.

Application areas:

Cutting, Sawing, Turning, Milling, Drilling

Ord.-no: 401114

Quality & properties

- Protects and lubricates the tool
- Reduces wear of the tool
- Non corrosive
- Silicone-free
- Simple application

Physical & chemical data

- Base: Mineral oil with additives
- Colourname: transparent, slightly brown
- Surfaces: tool
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Spray tools and material abundantly before machining.
- The tool / material must always remain moist during processing.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.