

presto Body Cavity Protection

Technical Information



presto Body Cavity Protection on a wax basis effectively protects cavities on the car body that are particularly susceptible to rust, such as doors, side panels, boot lids, bonnets etc. from rust build-up. Regular treatment can prevent rust damage at an early stage. A thin layer is sufficient to protect metals.

The aromatic-free sealant has an excellent water-displacing and penetrating effect. After application, a slightly sticky film with self-healing properties is obtained. If the applied layer warms up from the sun or engine heat, the typical smell of conventional waxes does not develop. The products are available in 500 ml spray can and 1 litre spray gun can.

Ord.-no: 603277, 306055

Quality & properties

- Excellent creeping properties in inaccessible cavities
- Infiltration and displacement even of existing water
- Easy application
- Self-healing property due to flow in case of minor damage
- Aromatics-free quality
- Anti-corrosion properties
- Water-repellent
- Excellent adhesion
- Resistant to weathering, weak acids and bases
- Product is not overpaintable

Physical & chemical data

- Base: Special combi resin
- Colourname:
 - brown
 - transparent
- Flash point:
 - 28
 - n.a.
- Storage stability:
 - 5 y
 - 10 y
- Content:
 - 1,00 L
 - 500 ML

How to use

For best results bring can to room temperature.
 Operational temperature 5 to 30°C.
 Surface should be clean, dry and free of grease.
 Shake well before use.
 Cover the areas not intended for coating.
 Application spray can: Shake can before use for approx. 2 minutes, and from time to time during use. Apply generously in the hollow areas by means of the adapter. Turn can after use and spray empty to clean valve.
 Application spray gun can: The product is ready-to-use, no thinner necessary. Application with a pressure pot gun with an air-pressure of 4-7 bar. Clean the spray gun with white spirit

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.