

presto Inox Spray

Technical Information



presto Inox-Spray is a reliable corrosion protection as well as a surface coating. Seals weld spots and weld seams. Also applicable as corrosion protection during spot-welding between car body sheets.

Overcoatable with all common paint systems, e.g. acrylic, synthetic, epoxy resin or nitro combi lacquers.

Ord.-no: 322532

Quality & properties

- High-grade nitro combi quality with metallic pigments
- Excellent coverage
- Quick-drying
- Excellent resistance to weathering
- Over-coatable
- Very good flow
- Light-proof / UV resistant
- Very hard surface

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: silver
- Efficiency: 400 ML – 0.8-1.0 m²
- Dry to touch: 20 min
- Dust dry: 5 min
- Overcoatable: 2 h
- Surfaces: welding spots, welds
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Surface should be clean, dry and free of grease.
- Sand if needed.
- Spray several thin coats in a crosswise motion.
- After every coat allow to dry for approx. 3 - 5 minutes.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.