

presto Plastic putty styrene-free

Technical Information



presto Putty for plastics "styrene-free" is a 2-component black polyester putty as a mixture of a highly elastic, amino-pre-accelerated polyester resin with different mineral, environment-friendly fillers. To fill scratches and damages and to aftertreat bonded plastic parts. Through its thixotropy and softness, profiles and contours can easily be rebuilt. The putty adheres to all plastics commonly used on the vehicle, such as PP, PUR, ABS, PA, PVC. Besides the very good adhesion on nearly all plastics, the putty can also be applied on carbody sheets and zinc coated sheets.

Ord.-no: 443732, 443800

Quality & properties

- High elasticity
- Easy to sand
- Easy processing
- Very good adhesion
- Pore-free
- Free of asbestos and silicone
- Resistant to weak acids and bases, propellants, solvents, water and de-icing salt

Physical & chemical data

- Base: Polyester resin
- Colourname: black
- Completely dry: 30 - 40 min
- Overcoatable: 30 - 40 min
- Surfaces: metal, various plastics, wood, concrete
- Minimum Working Temperature: 12 °C
- Maximum Working Temperature: 30 °C
- Flash point: 52
- Storage stability: 1.5 y
- Content:
 - 250 G
 - 1,00 KG

How to use

The area to be repaired should be derusted, clean, dry, free of grease and sanded.
 The putty adheres to all plastics commonly used on the vehicle such as PP, PUR, ABS, PA, PVC. Not suitable for weak plastics!
 Take the required amount of material from the can and mix it well with the corresponding quantity of hardener.
 Apply the mixed material in the desired layer thickness.
 After approx. 30 minutes the repaired spot can be drilled, sanded, sawed, rasped and painted.
 Clean tools immediately after use, if necessary with a nitro thinner.
 Do not return mixed material into the can.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.