

## presto Zinc repair

## Technical Information



Ideally suited to repairing and colour matching minor damage to galvanised steel surfaces.

For use on:

Doors, fittings, fences, gutters, drainpipes, crash barriers and containers

Ord.-no: 211874

### Quality & properties

- Fast drying
- Good coverage
- Lightfast and UV-resistant
- High surface hardness
- Excellent adhesion
- Scratch-free
- Resistant to petrol, diluted bases, acids and weather influences

### Physical & chemical data

- Base: Special resin
- Colourname: silver
- Efficiency: 400 ML – 1.25-1.75 m<sup>2</sup>
- Dry to touch: 10 - 20 min
- Overcoatable: 2 h
- Surfaces: galvanised steel, welding seams, corrosion-prone metals
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

### How to use

- The surface must be clean, dry, rust and grease free.
- Shake can for 2 minutes before use.
- Test spray at an invisible spot.
- Spray several thin layers from a distance of approx. 25 cm.
- Shake can between the coats, to avoid that the pigments settle out.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.