

presto Ceramic Paste Spray

Technical Information



Metal-free high-temperature paste with excellent lubricating effect. Good corrosion protection. Ideally suited for assembly work on ABS brake systems as well as for long-term lubrication of highly loaded sliding surfaces of all kinds. Temperature resistant from -40 ° C to + 1,400 ° C. The removable brush head allows for easy even application of the paste.

Application areas:

ABS braking systems, bayonet, plug and screw, pipe, flange joints and fittings

Ord.-no: 446832

Quality & properties

- Metal-free lubrication with extreme temperature resistance
- Facilitates dismantling, even after long periods of operation
- Prevents corrosion and squeaks
- Resistant to chemicals and weathering
- Non-conductive
- Resistant to salt water, weak acids and bases

Physical & chemical data

- Base: Special resin
- Colourname: white
- Surfaces: ABS brake systems, bayonet, plug and screw connections, pipe, flange and valve fittings
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can vigorously before use.
- Surface should be clean, dry and free of grease.
- Spray on the surface without the brush and then spread the paste evenly with the brush head.
- Make sure the friction areas are not sprayed!

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.