

presto Turpentine Substitute

Technical Information



presto Turpentine Substitute is used as a diluent for commercial synthetic resin paints, wood stains, anti-rust and Undercoats. It solves contamination of equipment, wood and linoleum floors.

Ord.-no: 171697, 171703

Quality & properties

For thinning oil and synthetic resin varnishes, wood glazes, rust protection and priming paints
Also used to clean brushes, rollers and brushes
Also ideal for removing color and dirt stains from parquet, linoleum and solvent-resistant floors

Physical & chemical data

Colourname: transparent
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 30 °C
Storage stability: 5 y
Content:
◦ 500 ML
◦ 1,00 L

How to use

Use sparingly.
Stir well into the paint to be thinned.
Follow the instructions of the paint manufacturer.
If in doubt, please carry out a preliminary test.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.