

presto Alu putty styrene-free

Technical Information



presto Aluminium Putty "styrene-free" is a 2-component polyester filling putty as mixture of a medium-elastic, highly reactive, amino-preaccelerated polyester resin with different mineral, environment-friendly fillers and aluminium pigments.

Applicable as filling compound for car repair, engine construction and for hobby works. Everywhere, where a large-area spreading is desired. Surfaces like metal, wood, div. plastics and concrete are easy to fill in the desired layer thickness. To fill and level out holes and to stabilise flimsy spots.

Ord.-no: 443596, 443602

Quality & properties

Highly thixotropic, therefore very easy wide-spread and pore-free application
Easy processing
Very good adhesion
High elasticity
Easy to sand
Free of asbestos and silicone
Resistant to weak acids and bases, propellants, solvents, water and de-icing salt

Physical & chemical data

Base: Polyester resin
Colourname: light grey
Completely dry: 30 - 40 min
Overcoatable: 30 - 40 min
Surfaces: metal, various plastics, wood, concrete
Minimum Working Temperature: 12 °C
Maximum Working Temperature: 30 °C
Flash point: 52
Storage stability: 1.5 y
Content:
◦ 250 G
◦ 1,00 KG

How to use

The area to be repaired should be derusted, clean, dry, free of grease and sanded.
As a primer before and after filling we recommend the presto Epoxy Primer (please note the drying time).
Take the required amount of material from the can and mix it well with the corresponding quantity of hardener.
Apply the mixed material in the desired layer thickness.
After approx. 40 minutes the repaired spot can be drilled, sanded, sawed, rasped and painted.
To prepare the subsequent painting we recommend to equalise the surface with prestol Filling compound or with presto Fine Putty.
Clean tools immediately after use, if necessary with a nitro thinner.
Do not return mixed material into the can.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.