

presto Penetraing Oil

Technical Information



presto Penetraing Oil is a powerful special oil that penetrates, thanks to its high creeping ability, into the finest and narrowest gaps and threads and effectively eliminating friction and squeaking noises. It infiltrates rust and loosens stuck screws, nuts, bolts and other fasteners, etc. The special recipe with high-quality graphite and MoS₂ ensures perfect, lasting lubrication. Metal, rubber and many plastics are not attacked by presto penetrating oil.

Application areas:

Lubricates, protects and cares all moving parts.

Ord.-no: 484902

Quality & properties

- High penetrability
- Contains MOS₂ and graphite
- Long-lasting lubricating effect
- Fast and effective
- Good penetration
- Non- corrosive
- Excellent adhesion
- Good corrosion protection
- Powerful, directed jet spray
- Moisture repellent

Physical & chemical data

- Base: Special resin
- Colourname: graphite/black
- Surfaces: movable parts
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: 0 °C
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Operating temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- Remove loose rust with a wire brush.
- Spray parts and leave to take effect.
- Starts working in most cases within 5 to 15 minutes, depending on the ability of the product to penetrate.
- Dirt and rust can already be removed from stuck parts after 5 minutes.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.