

presto Super Fastwax

Technical Information



Achieves incredibly fast long-term protection and top gloss in one step - no power-consuming polishing. High-quality maintenance product. Ideal to restore the gloss of lacquered surfaces, both metallic and non-metallic.

Ord.-no: 383403

Quality & properties

- Long-term protection
- Gives a glossy result
- Protects against weather influences
- Reduces the adhesion of dirt
- Contains silicone

Physical & chemical data

- Base: Special resin
- Colourname: transparent
- Surfaces: painted metallic and non-metallic surfaces.
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Storage stability: 5 y
- Content: 500 ML

How to use

- Shake before use.
- Do not use in the blazing sun.
- The surface should be clean and dry.
- Apply presto Super Fastwax with a moist cloth in a thin, equal layer and allow to dry.
- Polish to high gloss with a dry, soft cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.