

## presto BOB Rust Sealant

## Technical Information



presto BOB Sealing is a product for the preparation of rusted surfaces on the basis of moisture curing polyurethanes. Cures and isolates quickly, easily and safely all rusted surfaces.

The optimal basis for the subsequent priming with presto BOB Rust Protection Primer.

**Ord.-no:** 603710

### Quality & properties

- Quick, simple and safe application
- Hardens and isolates rusted surfaces
- Prevents further corrosion of the treated parts

### Physical & chemical data

- Base: Special combi resin
- Colourname: yellowish-transparent
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 30 °C
- Flash point: 13
- Storage stability: 3 y
- Content: 100 ML

### How to use

- Remove loose flakes of rust, subsurface rusted paints, dirt and fat.
- Do not apply during temperatures lower than +15°C.
- Generously apply the BOB Rust Sealing on dry or even on damp surface.
- Coat with presto BOB Rust Protection Primer earliest after 8 hours, but latest after 24 hours drying time, at best in 2 coats.
- Please consider: do not dilute the presto BOB Rust Sealing.
- Where appropriate, fill minor quantities in a smaller container to avoid that soiling or humidity let dry the material in the original can.
- Clean soilings immediately with an universal thinner.
- Surface remains slightly sticky.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.