

presto Smoke Detector Testspray

Technical Information



presto Smoke Detector Testspray is an effective test spray with the optical and photoelectric smoke detector reliably and quickly can be tested without additional test equipment.

Application areas:

Households, industry, trade, public buildings

Ord.-no: 416606

Quality & properties

For optical and photoelectric smoke detectors
Sprays a fine mist
Leaves no residues
Easy and fast test method without additional test equipment
Oil-free

Physical & chemical data

Base: See MSDS
Colourname: transparent
Minimum Working Temperature: 5 °C
Maximum Working Temperature: 30 °C
Flash point: n.a.
Storage stability: 10 y
Content: 150 ML

How to use

Bring the can to room temperature.
Operating temperature 15° to 35°C.
Shake can before use.
Keep the Test spray straight up and at a distance of 25 to 30 cm for a few seconds (5 seconds) spray in the direction of the smoke detector.
The reaction starts at a properly functioning detector within a few seconds.
If there is no response, repeat the test.
If despite repeated examination no reaction, so please check the battery first.
After continued lack of reaction, the defective smoke detector must be replaced.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.