

presto Wet Leak Finder

Technical Information



White powder spray for locating leaks of oil, fuel or other liquids. Enables easy and fast precise detection of leaks on car body, radiator, engine block, gearbox housing, power steering, fuel lines, pipes, pumps, etc. Easy to remove after application.

Ord.-no: 529832

Quality & properties

- Easy to remove after application
- Grease- and silicone-free
- Fast and safe application
- Economical in use
- Does not attack lacquers, rubber and plastics

Physical & chemical data

- Base: Special combination
- Colourname: white
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

How to use

- Bring the can to room temperature.
- Application temperature 5° to 30°C.
- Shake can for 2 minutes before use.
- The area to be tested should be clean and dry.
- Apply the spray to the suspected area to detect the leakage.
- Spray distance approx. 25 cm.
- Spray on evenly and allow to dry well.
- On the forming powder coating leaks are clearly visible.
- Then wash off thoroughly with water.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.