

## presto Marten Protection Spray

## Technical Information



presto Marten Protection Spray protects cable and wires from marten damage. It forms a sticky protective film that martens avoid. Highly effective ingredients allow moving parts to be sprayed.

**Ord.-no:** 803857

### Quality & properties

- Long-lasting protection
- Odourless
- Resistant to extreme temperature swings (-30°C to +250°C)
- Excellent adhesion
- Direct jet spray
- Resistant to effects of weather, weak acids and bases

### Physical & chemical data

- Base: Polyalphaolefine
- Colourname: transparent
- Surfaces: cables and wires
- Minimum Working Temperature: 5 °C
- Maximum Working Temperature: 30 °C
- Flash point: n.a.
- Storage stability: 10 y
- Content: 400 ML

### How to use

Bring the can to room temperature.  
 Operating temperature 5° to 30°C.  
 Shake can for 2 minutes before use.  
 Before using the product, the engine room has to be thoroughly cleaned. Use presto engine cleaner.  
 Then generously apply marten protection spray to the rubber and plastic parts to be treated in the engine room and flash off for at least 5 minutes.  
 To guarantee long-lasting protection, repeat the process every 2 months.  
 If a marten infestation has occurred, then the engine should be cleaned before applying marten protection.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.