



presto Filling compound styrene-reduced

Ord.-no.: look at ordering information



Technical Information

presto Filling compound "styrene-reduced" is a 2-component polyester filling putty as mixture of a medium-elastic, highly reactive, amino-preaccelerated polyester resin with different mineral, environment-friendly fillers. Applicable on metal, wood, concrete. To fill holes and unevennesses, to rework pretreated surfaces during repair on car body parts and other metal surfaces, for reconditioning and restoration of wood or concrete surfaces, e.g. steps of stairs, fitting of anchor bolts and screws etc. For universal use in the entire hobby and DIY sector.

Quality & properties

- Easy processing
- Quick, time-saving handling
- Very good adherence on different surfaces
- Easy to sand, even after a longer period
- Suitable for stoved enamel coating
- Free of asbestos and silicone
- Resistant to weak acids and bases, propellants, solvents, water and de-icing salt

Physical & chemical data

- Base: Polyester resin
- Colourname: ochre
- Consistence: good filling properties
- Completely dry: 30 min
- Further processed: 30 min
- Overcoatable: 30 min
- Sandable: 30 min
- Surfaces: metal, various plastics, wood, concrete
- Minimum Working Temperature: 12 °C
- Maximum Working Temperature: 30 °C
- Relative density: 1.86 g/cm³
- Pot life: 5 - 6 min
- Addition of hardener: 2 - 4 %
- Storage stability: 1.5 y
- Content:
 - ◊ 250 G
 - ◊ 1,00 KG
 - ◊ 2,00 KG
 - ◊ 500 G
 - ◊ 6,00 KG

How to use

- The area to be repaired should be derusted, clean, dry, free of grease and sanded.
- As a primer before and after filling we recommend the presto Epoxy Primer (please note the drying time).
- Take the required amount of material from the can and mix it well with the corresponding quantity of hardener.
- Apply the mixed material in the desired layer thickness.
- After approx. 30 minutes the repaired spot can be drilled, sanded, sawed, rasped and painted.
- Clean tools immediately after use, if necessary with a nitro thinner.
- Do not return mixed material into the can.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +49 (0) 62 66 75-266 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com